

บริษัท อัมรินทร์เซรามิกส์คอร์ปอเรชั่น จำกัด
27/1 Moo 3 Tambon Lampoo, Bang-Bua Thong
Nontaburi 11110

Tel: 0-2961-7224-5, Fax 0-2961-7267

Email : info@amarinceramics.com

Website : www.amarinceramics.com

Technical Data Sheet

Effect Liquid Glaze Series EL

Effect Liquid Glaze Series EL is water-based ready used glaze to create variety of effects. Glaze can be applied by brushing and dipping. Glaze is developed for oxidation firing which recommend for pottery and art work. The layer thickness of raw glazed will be different with fire result. These EL series can be coated over each item, then users are able to trial mixing glaze in series to achieve more interested result, special character and unique charm depend on mixing ratio of glazes.

Application

1. Shake well before use.
2. Brushing or dipping on biscuit (fired clay around 800 °C without glaze). Recommend to brushing 2-3 layers or dipping more thick than typical glazes to get the beautiful result after firing.
3. Can fire with typical glaze at firing temperature 1,200 °C-1,230 °C. Recommend putting away from others at least 2 inches.

High running glaze should be careful, to prevent glaze sticking during final firing by apply thinner layer of glaze at bottom of work piece and apply glaze higher than bottom at least 2 inches or apply typical glaze at the bottom.

Product Detail

EL-1100 Cloudy Blue **High running glaze, be careful**
EL-1101 Deep Azure
EL-1130 Copper Flint
EL-1131 Mahogany
EL-1132 Brown Sugar
EL-1140 Lucky Green
EL-1180 Galaxy
EL-1181 Phantom